

### Get comfortable with the

# camino

## wood pellet fire





The Camino wood pellet fire combines the latest in technology with classy Italian styling. A heating appliance that is not only attractive to look at, but provides comforting heat delivered quickly, distributed effectively, with modern conveniences such as a remote control, timer and thermostat.

- 88% Efficient
- 8.2kW max. heat output
- Runs on renewable, sustainable, wood pellet fuel
- Italian design & style
- Push button technology for easy operation
- Proven performance in Europe, now available in New Zealand.





#### St Elmos Fire

#### Features & Benefits


- Flush mounted insert design ideal for installation in a new home, stylish, visual and space saving.
- Easy refuelling
   unit slides forward easily and smoothly to allow for easy
   refuelling.
- Remote, Timer & Thermostat controls
  manage heat using a remote control and thermostat or set
  your fire to turn off/on according to time
- Burns renewable, NZ made, low emission pellet fuel
   virtually smoke free combustion for healthy, clean air
- Automatic ignition
   easy to use for cleaner, faster, 'no fuss' warmth
- Highly efficient produces virtually no smoke and leaves very small amounts of ash
- Clean Air approved, National Environmental Standards
- Selection of Surrounds


Choose a surround to complement your decor, or have a custom surround designed to give you a unique look that is all your own.



- Made in NZ from natural untreated radiata pine wood waste
- Economical
- Low moisture high in energy
- Clean and easy to store
- Great for the planet

#### Dimensions





#### Performance

Efficiency	88%
Maximum heat output	8.2kW
Hopper capacity	17kg
Living Area	*Average - large


\*Average - large

\* Subject to insulation levels

# 705

#### Clearance to combustibles

#### Side View




**Note:** The front of the enclosure needs to be made of a suitable fire proof rated board above 80°C eg Micore, Superlux, Eterpan or similar. Ventilation of min 100cm² will be required into the cavity.

Location	Dimension (mm)
А	1210
В	330 (min)
С	1105
D	220
Е	150
F*	110
G	350-580

\*from exhaust spigot to combustible wall

#### Bird's Eye View



Note: Built-in fire clearances don't apply in a non-combustible cavity. The above clearance to combustibles for the flue are only applicable within the fire envelope. Clearance outside this eg at a ceiling/wall thimble reverts to 25mm as per ARS flue test 05/1185. Correct as at September 2015.





Heatstore New Zealand Ltd 472 Blenheim Road, Christchurch (Cnr Watts & Blenheim Roads) Ph: 03 343 1651 www.heatstore.co.nz

